



## Butterfly Hanger for 5 in coaxial cable and elliptical waveguide 20

### Product Classification

<b>Product Type</b>	Hanger kit
<b>Ordering Note</b>	CommScope® non-standard product

### General Specifications

<b>Cable Type</b>	Corrugated
<b>Cables per Hanger</b>	1
<b>Color</b>	Silver
<b>Hanger Type</b>	Standard butterfly hanger
<b>Mounting</b>	1/2 in threads

### Dimensions

<b>Height</b>	41.91 mm   1.65 in
<b>Width</b>	38.1 mm   1.5 in
<b>Length</b>	63.5 mm   2.5 in
<b>Compatible Diameter, maximum</b>	132.08 mm   5.2 in
<b>Compatible Diameter, minimum</b>	127 mm   5 in
<b>Nominal Size</b>	5 in

### Electrical Specifications

<b>Return Loss Effect</b>	0.1 dB
<b>DTF Effect</b>	0.1 dB

### Material Specifications

<b>Material Type</b>	Galvanized steel
----------------------	------------------

# 33598-5

---

## Mechanical Specifications

**Vibration Survival** =4 hours at resonant frequency

## Environmental Specifications

**Operating Temperature** -40 °C to +85 °C (-40 °F to +185 °F)

**Corrosion Resistance, minimum with no degradation** =500 hours in salt spray chamber

**Environmental Strength Capability** Double cable weight

## Packaging and Weights

**Height, packed** 36.8 cm | 14.488 in

**Width, packed** 11 cm | 4.331 in

**Length, packed** 11 cm | 4.331 in

**Packaging quantity** 10

**Weight, gross** 2.11 kg | 4.652 lb

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant

