


# PM-SU2L-B



Universal Adjustable Sliding Pipe Mount Kit for 2-3/8 in OD pipe, 6-14 in stand-off



## Product Classification

**Product Type** Pipe mount

## Dimensions

**Mounting Diameter, maximum** 203.2 mm | 8 in  
**Mounting Diameter, minimum** 0.0 mm | 0 in  
**Pipe Outer Diameter** 60.3 mm | 2 3/8 in  
**Height** 127.0 mm | 5.0 in  
**Length** 304.8 mm | 12.0 in  
**Weight** 40.9 kg | 90.2 lb  
**Width** 304.8 mm | 12.0 in

## Environmental Specifications

**Wind Rating** 120 mph (BWS) at 150 ft AGL  
**Wind Rating Test Method** TIA/EIA-222

## General Specifications

**Pipe, quantity** 0  
**Stand-off Distance** 355.6 mm | 14.0 in  
**Tower Taper** Non-tapered | Tapered  
**Includes** Sliding pipe mount brackets | Universal saddle mount  
**Material Type** Hot dip galvanized steel  
**Mounting** Angle 60°, 203.2 mm (8 in) | Angle 90°, 152.4 mm (6 in) | Straight or tapered legs up to 203.2 mm (8 in) OD  
**Note** One 96 in x 8 in panel antenna per sector  
**Package Quantity** 1  
**Stand-off Distance, adjustable** 6-14 in | 15.2-35.6 cm

## Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



## \* Footnotes

### **Wind Rating**

BWS—Base Wind Speed; FBC—Florida Building Code