SHK-158-1-P



Single Hanger Kit for 1-5/8 in coaxial cable, single stack; includes hardware and angle adapter

Product Classification

Product TypeHanger kitProduct BrandValuSite™

Ordering Note CommScope® standard product in Asia Pacific

General Specifications

Cables per Hanger 1

Color Black

Hanger TypeComposite clampMountingM8 hardware

Dimensions

Maximum Stack Height 1

 Height
 78.994 mm | 3.11 in

 Width
 25.908 mm | 1.02 in

 Length
 90.424 mm | 3.56 in

Compatible Diameter, maximum 50.8 mm | 2 in

Compatible Diameter, minimum 49.022 mm | 1.93 in

Nominal Size 1-5/8 in

Electrical Specifications

 Return Loss Effect
 0.1 dB

 DTF Effect
 0.1 dB

Material Specifications

Material Type Engineered plastic | Stainless steel

Page 1 of 2

SHK-158-1-P

Mechanical Specifications

Vibration Survival ≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C} \text{ to } +85 \,^{\circ}\text{C} \, (-40 \,^{\circ}\text{F to } +185 \,^{\circ}\text{F})$

Corrosion Resistance, minimum with no degredation ≥500 hours in salt spray chamber

Environmental Strength CapabilityDouble cable weight

UV Resistance, minimum with no degradation ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

 Height, packed
 38.1 cm | 15 in

 Width, packed
 38.1 cm | 15 in

 Length, packed
 7.6 cm | 2.992 in

Included Angle adapter | Hardware

Packaging quantity 1

Weight, gross 0.57 kg | 1.257 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

