



Universal Snap-in Hanger for 7/8 in corrugated, smoothwall, and braided coaxial cable

Product Classification

Product Type	Hanger kit
Product Brand	I-Line
Ordering Note	CommScope® non-standard product

General Specifications

Cables per Hanger	1
Color	Silver
Hanger Type	Snap-in hanger
Mounting	3/4 in drilled cable ladder

Dimensions

Height	40.894 mm 1.61 in
Width	37.084 mm 1.46 in
Length	71.12 mm 2.8 in
Compatible Diameter, maximum	30.988 mm 1.22 in
Compatible Diameter, minimum	26.67 mm 1.05 in
Nominal Size	7/8 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

Material Type	Stainless steel
----------------------	-----------------

252115

Mechanical Specifications

Vibration Survival =4 hours at resonant frequency

Environmental Specifications

Operating Temperature -40 °C to +85 °C (-40 °F to +185 °F)

Corrosion Resistance, minimum with no degradation =500 hours in salt spray chamber

Environmental Strength Capability Double cable weight

Packaging and Weights

Height, packed 17 cm | 6.693 in

Width, packed 13 cm | 5.118 in

Length, packed 10 cm | 3.937 in

Packaging quantity 10

Weight, gross 0.44 kg | 0.97 lb

Regulatory Compliance/Certifications

Agency	Classification
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant