

FA-104212-SIH



HELIAX® Hanger Kit, 4 holes x 10.0 mm (FJ-2SM-series cables) and 2 holes x 21.0 mm (PWRT-608-S cables) grommet, 1 x 252118 Snap-in hanger

HELIAX® FiberFeed® Hanger Kit, 4 holes x 10.0 mm (FJ-2SM-series cables) and 2 holes x 21.0 mm (PWRT-608-S cables) grommet, 1 x 252118 Snap-in hanger (designed to organize multiple cables, not intended to support the weight of the cable for long vertical runs up a tower)

Product Classification

Product Type	Hanger kit
Product Brand	HELIAX®

General Specifications

Cables per Hanger	6
Color	Black Silver
Hanger Type	Hanger kits
Mounting	3/8 in (M10) drilled cable ladder

Dimensions

Height	57.912 mm 2.28 in
Width	63.5 mm 2.5 in
Nominal Size	2-1/4 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

Material Type	Stainless steel
----------------------	-----------------

Mechanical Specifications

Vibration Survival	=4 hours at resonant frequency
---------------------------	--------------------------------

FA-104212-SIH

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Corrosion Resistance, minimum with no degradation	=500 hours in salt spray chamber

Packaging and Weights

Height, packed	26 cm 10.236 in
Width, packed	9 cm 3.543 in
Length, packed	9 cm 3.543 in
Packaging quantity	10
Weight, gross	0.53 kg 1.168 lb

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

