


FPH-510-924-6-100



Blockchain Cable Hanger for three 5 to 10mm fiber cables and three 9 to 24mm power cables, pack of 100

Product Classification

Product Type	Hanger kit
Product Brand	ValuSite™
Ordering Note	CommScope® standard product in Asia Pacific CommScope® standard product in Europe, the Middle East, and Africa CommScope® standard product in Mexico, Central America, and South America

General Specifications

Cables per Hanger	6
Color	Black
Hanger Type	Composite clamp
Mounting	M6 hardware

Dimensions

Maximum Stack Height	3
Height	155.575 mm 6.125 in
Width	28.702 mm 1.13 in
Length	104.775 mm 4.125 in
Compatible Diameter, maximum	24.002 mm 0.945 in
Compatible Diameter, minimum	5 mm 0.197 in

Electrical Specifications

Return Loss Effect	0.1 dB
DTF Effect	0.1 dB

Material Specifications

Material Type	Engineered polymer Galvanized steel
----------------------	---------------------------------------

Mechanical Specifications

FPH-510-924-6-100

Vibration Survival

≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature

-40 °C to +85 °C (-40 °F to +185 °F)

Corrosion Resistance, minimum with no degradation

≥500 hours in salt spray chamber

Environmental Strength Capability

Double cable weight

UV Resistance, minimum with no degradation

≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Height, packed

28.6 cm | 11.26 in

Width, packed

15.2 cm | 5.984 in

Length, packed

25.4 cm | 10 in

Included

Angle adapter | Hardware

Packaging quantity

10

Weight, gross

0.48 kg | 1.058 lb

* Footnotes

Maximum Stack Height Fiber, Hybrid, Power