Mini Block Hangers, 5-8 mm for Fiber, 9-14 mm for Power Cable, Kit of 10



Product Classification

Product Type Hanger kit

Ordering Note CommScope® Standard Product in Europe | Not available in the United

States or Canada

General Specifications

Accessories Hangers

Cables per Hanger 2

Color Black

Hanger Type Double block hanger

Mounting M10 compatible through hole | M8 compatible through hole

Dimensions

Maximum Stack Height 3

 Height
 35.052 mm | 1.38 in

 Width
 10.414 mm | 0.41 in

 Length
 48.006 mm | 1.89 in

 Compatible Diameter, maximum
 13.995 mm | 0.551 in

 Compatible Diameter, minimum
 5.004 mm | 0.197 in

 Diameter Range (cable 1)
 9.00-14.00 mm

 Diameter Range (cable 2)
 5.00-8.00 mm

Electrical Specifications

Return Loss Effect 0.1 dB **DTF Effect** 0.1 dB



FPH-58-914

Material Specifications

Material Type Engineered plastic

Mechanical Specifications

Vibration Survival ≥4 hours at resonant frequency

Environmental Specifications

Operating Temperature $-20 \, ^{\circ}\text{C} \text{ to } +80 \, ^{\circ}\text{C} \, (-4 \, ^{\circ}\text{F to } +176 \, ^{\circ}\text{F})$

Environmental Strength Capability Double cable weight

UV Resistance, minimum with no degradation ≥100 hours exposure in accelerated UV life chamber

Packaging and Weights

Packaging quantity 10

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power