

AC Surge Protector SPD I2R-T125 DIN-Rail 230 Vac 3-Phase Wye MOV 100 kA, IEC 61643-11 Class I+II, CE, RoHS

I2R-T125-3P230



Features

- IEC61643-11 Class I+II
- High Capacity MOV Protection
- · Visual Suppression Status Indicator
- Dry Contact Remote Annunciation Terminals

Applications

- · Electrical Panelboards
- Industrial Automation
- · Communications Base Stations
- IT & Data Centers
- Switchgear
- · Motor Control Centers
- · Automatic Transfer Switches

- Replaceable Suppression Modules
- · Wire and Comb Busbar Wiring Terminals
- · Reversible Chassis for Top or Bottom Wiring
- DIN-Rail Mount
- Wastewater Treatment
- · Oil & Gas
- · LED Lighting
- Schools
- Hospitals
- Mining
- · Photovoltaic and Wind

Description

AC surge protector (also known as SPD or lightning protector) I2R-T125-3P230 from Transtector is a DIN-Rail style SPD that utilizes state of the art MOV technology to protect critical equipment that operates on a 230 Vac 3-Phase Wye electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector AC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		230		Vac
Service Type		3-Phase Wye		
Frequency	50		400	Hz
Maximum Continuous Operatii	ng Voltage (MCOV)			
L-N			275	Vac
Backup Fuse		315		A gL/gG

Surge Protection Specification

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: AC Surge Protector SPD I2R-T125 DIN-Rail 230 Vac 3-Phase Wye MOV 100 kA, IEC 61643-11 Class I+II, CE, RoHS I2R-T125-3P230



AC Surge Protector SPD I2R-T125 DIN-Rail 230 Vac 3-Phase Wye MOV 100 kA, IEC 61643-11 Class I+II, CE, RoHS

I2R-T125-3P230



Surge Protection Technology	MOV		
Protection Modes	L-N		
8/20µs Surge Current		100	kA
10/350µs Surge Current	25		kA
Nominal Discharge Current Rating (In)	25		kA
VPR 8/20µs			
L - N		1,500	Vpk
Response Time		25	ns
SCCR (Short Circuit Current Rating)	25		kAIC

Mechanical Specifications

Size

Height 2.992 in [76 mm] Width 3.543 in [89.99 mm] Depth 4.252 in [108 mm] Weight 2.38 lbs [1.08 kg] Housing Material and Plating PA66 CT1; V-0

Environmental Specifications

Temperature Range (Operational) -40 to +80 deg C Temperature Range (Storage) -40 to +80 deg C **Environmental Protection Rating IP 20**

Humidity 95% non-condensing

Installation

DIN Rail Mount Type Service Wiring Terminal Compression Lug #1 to #9 AWG **Status Indication Terminal** 3-Position Screw Terminal #16 to #22 AWG

Compliance Certifications

RoHS Compliant Yes **CE** Compliant Yes

Certifications IEC 61643-11 Class I+II

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: AC Surge Protector SPD I2R-T125 DIN-Rail 230 Vac 3-Phase Wye MOV 100 kA, IEC 61643-11 Class I+II, CE, RoHS I2R-T125-3P230



AC Surge Protector SPD I2R-T125 DIN-Rail 230 Vac 3-Phase Wye MOV 100 kA, IEC 61643-11 Class I+II, CE, RoHS

I2R-T125-3P230



Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: AC Surge Protector SPD I2R-T125 DIN-Rail 230 Vac 3-Phase Wye MOV 100 kA, IEC 61643-11 Class I+II, CE, RoHS I2R-T125-3P230

URL: https://www.transtector.com/ac-surge-protector-spd-i2r-t125-din-i2r-t125-3p230-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transfector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transfector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transfector does not assume any liability arising out of the use of any part or documentation.

I2R-T125-3P230 CAD Drawing

