



THE POWERFUL DIFFERENCE

COMMANDER II/II+ DC POWER SYSTEMS

Ensure your site has power when it needs it most with the Commander II Series of DC power systems, the next generation of robust power plants.

The Commander II Series offers top of the line power and reliable performance while providing complete customizability when it comes to functionality, scale, and management. The system comes with a web-based monitoring and troubleshooting

platform entirely tailored to fit individual needs, providing a completely remote management tool that delivers realtime data at your fingertips.

This system offers hot-swappable modules for quick and easy deployment, minimizing installation time and maximizing uptime with a one-year warranty. Trust the Commander II & II+ for reliable and dependable DC power system to offer **The Powerful Difference.**

COMMANDER II SERIES FEATURES

- 19" rack mount shelf with integrated power distribution
- 90-250 VAC input, Power Factor Corrected
- Standard 4x 125A Battery Circuit Breakers
- Standard 18x 18mm 6A to 63A user selected Load Circuit Breakers
- Output temperature compensated for precise battery charging
- EM4x Controller with comprehensive controls (local and web UI), data collection and alarm monitoring/logging via v2 and v3 SNMP
- General Purpose Digital Inputs for user configured external alarms
- Hot swappable power bays
- Low Voltage Battery Disconnect built-in
- Easily configures to meet site power requirements

COMMANDER II

- 6U rack height with integrated cable management
- 12 power bays accept 3000W, -48V rectifiers
- 36kW max. output capacity @ -54VDC

COMMANDER II+

- 7U rack height with integrated cable management
- 8 power bays accept 3000W, -48V rectifiers
- 8 power bays accept 4800W. 12V or 24V DC-DC converters
- 28.8kW max. output capacity @ -54VDC