

Flex-Line Universal Steel Enclosures

14 x 12 x 6 or 12 x 10 x 6 in.

ventev®

Connect, Protect, and Enable™

Ventev's Flex-Line Universal Steel Enclosures provide NEMA 4 outside protection or NEMA 12 inside protection with solid door enclosures. Each enclosure offers a clean, seamless design to protect wireless equipment from damage caused by tampering or environmental elements. These versatile, rugged enclosures are constructed from 14-gauge steel and include eight knockouts for antenna ports and one for strain relief. Each knockout is only visible from the inside of the enclosure to enhance the exterior aesthetic design — making them excellent, durable enclosures for multiple applications as users upgrade from existing wireless equipment to new technologies.



Specifications

| | |
|---------------------|---|
| Size | 14 x 12 x 6 or 12 x 10 x 5 in. |
| Environment | Indoor/Outdoor |
| Locks | Key Lock |
| NEMA Rating | 4X and 12X |
| Material | 14 Gauge Steel |
| Self-Tapping Screws | 7/32 in. holes (qty. 4) |
| | 8/32 in. holes (qty. 14) |
| | 10/32 in. holes (qty. 2) |
| | 6/32 in. holes (qty. 2) |
| | 9/32 in. holes (qty. 4) |
| Mounting | Wall or Pole |
| Knockout* | 3/4 in. hole for strain relief (qty. 1) |
| | 1/2 in. holes for RPTNC connectors (qty. 6) |
| | 5/8 in. holes for N-Style connectors (qty. 2) |

* Note: Spurs in open knockouts may need to be filed down to fit jumpers.

Features & Benefits

Protects RF and networking equipment from elements, theft and tampering.

Clean, seamless design with knockouts for antenna ports inside the enclosure, but invisible on the outside surfaces.

Durable key lock for additional security benefits.


Flexible mounting options

Flex-Line Universal Steel Enclosures

14 x 12 x 6 or 12 x 10 x 6 in.

ventev®

Connect, Protect, and Enable™



Universal Mounting Plate



Knockouts for Antenna Ports



Enclosure Key Lock

Enclosure Construction

Body flange trough excludes liquids and contaminants.

Large perimeter opening facilitates component installation, maintenance or conversion.

Seamless gasket provides oil-tight and dust-tight seal against contaminants.

M6 base flange grounding stud on body. M6 base flange bonding provision on door.



Available Models

| Manufacturer Part Number | SKU | Size | Weight |
|--------------------------|--------|-----------------|-------------|
| T12106-KEY-S-8 | 313906 | 12 x 10 x 6 in. | 13.08 lbs. |
| T14126-KEY-S-8 | 313248 | 14 x 12 x 6 in. | 17.035 lbs. |

Included Accessories

Universal Mounting Plate

Self-Tapping Screws to Mount Wireless Products on Universal Mounting Plate

½" NEMA 4 Hole Seal (Plug) to Provide a Tight Seal on Unused Knockout Openings (qty. 2)

Strain Relief

Keys for Door Lock

Mounting Options

Enclosures may be mounted to poles using Ventev's enclosure pole mount kit (up to a 12 in. diameter).

SKU* 303580

*Fasteners are not included.



Flexible mounting options